



METCRAFT

RIS-STOP-2SF-R - 2" Pressure Overfill Prevention

Specifications:

Flow Rates:

10 - 600 litres per minute

Pressure range:

Effective at up to 8 bar maximum

Fluid Viscosity:

Effective with fuel / oil viscosity of ASE10 or lower for

IMPORTANT NOTE:

The RIS-STOP family of valves are not suitable alternatives for true "Shut off valves" and must not be used in continuously pressurised systems.

Suitable for above ground commercial diesel storage installations, and pressure deliveries. It incorporates many proven RIS-STOP features and now includes a more compact 4-bolt flanged inlet on the body allowing greater maximum tank fluid levels.

- Cartridge construction for easy installation and access via the 2" tank lid socket supplied
- Very high flow capacity (50% greater than some competitive products)
- Effective at low flow rates (10-600 l/m) Pressure delivery up to 8 bar maximum
- Two-stage shut off giving warning of complete closure over last 15mm of level change
- On-site inspection and testing via access cap without pipework dis-assembly
- No dynamic seals - promoting long service life
- Acts as anti-syphon valve in normally closed position
- Suitable for fuels of SAE10 or lower (other models available for higher viscosity)
- Compatible with all pipe-work brands
- Flexible connectors available: make fitting/servicing easier, remove stress from pipework

Materials:

Anodised Aluminium
Viton A (FKM)
Stainless Steel
HDPE closed cell foam



 Office Address:
Metcraft Group LTD
Unit 4, Cliffe Court
Medway City Business Estate
Rochester, Kent
ME2 4GU

 Factory Address:
Metcraft Group LTD
4 Old Mill Lane
Aylesford
Kent
ME20 7DT

 www.metcraft.co.uk
 contact@metcraft.co.uk
 +44 (0) 1903 714 226